

CA70BK REFILL INSTRUCTIONS For Canon® BC-60 Cartridge

Contents:

Your kit should contain the following:
2oz bottle of ink, 1oz bottle of clear activator fluid, 1 10cc injector, 1 30cc injector 2 sharp needles, cotton wipes, 1 drill tool, instructions.

If any of these items are missing please call us for a replacement item or kit.



***READ ENTIRE SET OF DIRECTIONS
BEFORE PROCEEDING***

PLEASE WORK ON
NEWSPAPER IN CASE OF SPILLAGE

- 1) This cartridge is special because of the clear activator fluid used in one of the chambers. The clear fluid will clot the black ink on contact so use caution when refilling this cartridge. 2 injectors are provided in the kit. Use the larger, 30cc injector **ONLY** for the black ink and the smaller 10cc injector **ONLY** for the clear fluid.
- 2) Locate the label on top of the cartridge and peel it back to expose the vent holes. Figure 1. Using the drill tool, enlarge the vent hole as shown. The vent hole is the smaller of the two. Drill all the way through the plastic case.
- 3) Attach the needle to the injector. ***CAUTION*** The needle is **VERY** sharp. Draw 15 – 20 cc of **BLACK** ink into the injector. Push the needle into the hole that you made in step #2. Insert the needle all the way, as far as it will go into the cartridge. Inject the ink slowly while pulling the needle out of the cartridge. This insures that the internal sponge is fully saturated.
- 4) Repeat the steps above for the clear activator fluid. Make sure that you inject the clear fluid in the correct chamber. Failure to observe caution here will result in a damaged and useless cartridge. **CLEAN THE DRILL TOOL THOROUGHLY BEFORE DRILLING THE CLEAR VENT HOLE.** Use 5 – 7 cc of clear fluid in the 10cc injector. Use a different needle. Replace the label over the vent holes.



FIGURE 1



FIGURE 2