

# HP870BK

## REFILL INSTRUCTIONS

For HP® 51645A BLACK

### Contents:

Your kit should contain the following:

4oz bottle of ink, 1 10cc ink injector, 1 polly wipe, 3 steel ball bearings, 4" needle, 4 black seals, push tool, instructions.

If any of these items are missing please call us for a replacement item or kit.



Fill Hole



(Figure 2)



(Figure 3)

### STEP 1

Set the cartridge to be filled on some newspaper in case of any ink spillage. Remove the tape that covers the fill hole. Push the steel ball into the cartridge with the golf tee provided. (Figure 2)

### STEP 2

Attach the needle to the injector/syringe and draw 10cc of ink. Dispense it slowly into the cartridge until it has taken the full amount. Do this 2 more times. Next, push one of the steel balls into the fill hole while squeezing the sides of the cartridge. (Figure 3)

### IMPORTANT

You **MUST** squeeze the sides of the cartridge while inserting the steel ball. Failure to do this will result in ink leaking out of the cartridge. The cartridge needs the negative pressure to retain the ink.

### TROUBLE SHOOTING

**PRINTS IN STREAKS / MISSING LINES** : Perform print head clean procedure as described in the owners manual.

**CARTRIDGE LEAKS:** Cartridge is not sealed properly. Reseal cartridge. The cartridge is overfilled. Place on a paper towel until it stops leaking. You forgot to squeeze the cartridge when you inserted the steel ball.

ATLASCOPY.COM  
P.O. Box 1292  
Dover, DE. 19904  
<http://atlascopy.com>